

Cube

Working surfaces e.g.: $1.05 \text{ m} \times 1.05 \text{ m} \times 1.55 \text{ m} / 1.05 \text{ m} \times 2.05 \text{ m}$

Traversing speed max. 15 m/minZ-axis

Z-axis clearance 100 mm

► Heavy-duty supports for workpieces up to 1,000 kg/m²

- Welded, stainless aluminum machine housing
- ▶ Recirculating ball bearing guide X and Y axes
- STM SmartCut waterjet cutting software
- ► Safety enclosure with automatic door
- Brushless servo motors
- ► CNC control NUM
- Control panel
- CNC Z-axis





Options:

- ► Manual cutting valve rotary holder for bevel cuts up to 48°
- Sedimentation tank with pressure bag filter for overflow
- ► STM BasicClean or STM OneClen washout systems
- ► STM TAC 12° bevel cut compensation cutting head
- Abrasive storage tank for 450 kg or 1,650 kg
- Automatic water level control
- Drilling spindle pneumatic

STM Waterjet Group partnership, precision and performance

STM WATERJET GMBH AUSTRIA

5531 Eben im Pongau, Austria
T: +43 6458 200 14-0
W: www.stm-waterjet.com
E: info@stm.waterjet.com

STM WATERJET AG SWITZERLAND

6260 Reiden, Switzerland T: +41 62 772 44 44 W: www.stm-waterjet.ch E: info.ch@stm-waterjet.com